

▼ Shown: Cross Bearing Puller Set BHP361G



- Precise hydraulic control allows fast, efficient and safe pulling
- High quality, forged steel components provide superior reliability and service.

BHP Series

Capacity:

6, 11, 16 and 22 ton

Reach:

357 - 864 mm

Spread:

260 - 580 mm

Maximum Operating Pressure:

350 bar



CAUTION! Not all puller components and configurations are rated at the set capacity. Please contact Enerpac for details.

Cross Bearing Puller Sets

Hand Pump	XA11G Air Pump	PUD1300 Electric Pump	XC1201M Cordless Pump	
BHP162	BHP162A	BHP162EE *	BHP162CE *	
BHP261G	BHP261GA	BHP261GEE *	BHP261GCE *	
BHP361G	BHP361GA	BHP361GEE *	BHP361GCE *	
BHP561G	BHP561GA	BHP561GEE *	BHP561GCE *	

* E = 230 V pump. For 115 V change "E" suffix into "B".

▼ SELECTION CHART

Cross Bearing Puller Set Capacity		6 ton	11 ton	16 ton	22 ton	
	Model Number ▶	BHP162 ¹⁾	BHP261G	BHP361G	BHP561G	
	Set Weight ▶	26 kg	62 kg	121 kg	185 kg	
	Included Hydraulics					
	• Hand Pump	P142	P392	P392	P80	
	• Cylinder	RWH121900	RCH202	RCH302	RCH603	
	• Saddle	-	HP2015	HP3015	HP5016	
	• Hose	HC7206C	HC7206C	HC7206C	HC7206C	
	• Gauge + Adaptor	GA45GC	GA45GC	GA45GC	GA45GC	
20	Cross Bearing Puller ²⁾	Model Number ▶	BHP1772	BHP262	BHP362	BHP562
	Spread (mm)	Maximum	260	345	440	580
		Minimum	115	140	180	220
	Reach (mm)	Maximum	357	570	710	864
	Adjusting Screw (mm)	Diameter	3/4" - 16 UNF	1" - 8 UNC	1 1/4" - 7 UNC	1 5/8" - 5.5 UNS
		Length	400	675	795	975
	Leg (mm)	Length	105	239	203	609
		Length	357	419	457	863
		Length	-	571	711	-
		Length	-	114	-	-
	Upper Leg Ends (mm)	Thread	3/4" - 16 UNF	3/4" - 16 UNF	1-14 UNS	1 1/4" - 12 UNF
	Lower Leg Ends (mm)	Thread	5/8" - 18 UNF	5/8" - 18 UNF	1-14 UNS	1 1/4" - 12 UNF
30	Bearing Cup Puller ²⁾	Model Number ▶	BHP180	BHP280	BHP380	BHP580
40	Bearing Separator ²⁾	Model Number ▶	BHP181	BHP282	BHP382	BHP582
	• Wooden Case		CM6	CW187	CW350	CW750

¹⁾ Includes Adaptor FZ1055.

²⁾ Can be ordered separately without hydraulic components, see next page.