


4WLD

WIRE FEEDER



R.D. VINCENT (PTY) LTD REG. NO. 1975/004192/07 Trading as:
VINCENT INDUSTRIAL SUPPLIES
P.O. BOX 1249 48 INDUSTRIA CRESCENT TEL: 013 692 8151/2/3
WITBANK EXTENSION 25 FAX: 013 692 8154
1035 WITBANK dennis@vincentis.co.za
WEBSITE: <http://www.vincentis.co.za>

2 YEAR WARRANTY

500A 60% DUTY CYCLE @ 40°C

MICRO-PROCESSOR



STAR WELD

WELDING PRODUCTS

MADE IN SOUTH AFRICA

The Starweld range of 4WD wire feeders are micro processor controlled, offering a full variable, smooth, wire feed selection. In addition the feeder is fitted with both voltage and amperage controls, as well as a trigger lock function.

FEATURES

- ★ **Remote Voltage** - Control power source voltage remotely from wire feeder.
- ★ **Water Cooled Option** - On water cooled equipment, water quick couplers provided for torch inlet and outlet water flow.
- ★ **Dual Voltage Option** - Wire feeder available with an 110VAC and 24VAC supply input in order to operate off other brands of equipment.
- ★ **Long Base Option** - A longer wire feeder base is also available designed to carry a 27kg wire spool. Standard version has the capacity to carry a 15kg wire spool.
- ★ **4WD Motor** - Powerful 4 wheel drive motor suitable for wire diameters from 0.6mm to 3.2mm.
- ★ **Roller Options** - V, U and Knurled rollers available for different wire types.
- ★ **Ramp Up / Burnback** - Internally adjustable.
- ★ **2T / 4T** - 2 Step and 4 Step trigger selected via mode button.
- ★ **Robust Construction** - Components are securely mounted to enable the machine to operate in hazardous environments, including being mounted on generator sets.
- ★ **Two Year Warranty** - Warranty on all parts and labour.





R.D. VINCENT (PTY) LTD REG. NO. 1975/004192/07 Trading as:

VINCENT INDUSTRIAL SUPPLIES

P.O. BOX 1249 48 INDUSTRIA CRESCENT TEL: 013 692 8151/2/3
 WITBANK EXTENSION 25 FAX: 013 692 8154
 1035 WITBANK dennis@vincentis.co.za

WEBSITE: <http://www.vincentis.co.za>

Technical Specifications	4WD	
Input Voltage	24VAC / OTHER	
Input Current	3.5A	
Rated Output Voltage		
Rated Output Current	500A	
Duty Cycle @ 40°C Ambient	60%	
Dimension - W x H x L mm	280x360x590	
Spool Capacity	15kg - Std	27kg - LB