



Fibre Discs

Al-Ox

Aluminium Oxide

Designed for a wide range of applications. High speed penetration of tough and high tensile materials combined with long disc life and optimum flexibility ensure Kennedy sanding discs give first class performance every time. Recommended for use with all portable grinders and sanders.



Grit	Weight per 25	Order Code KEN-202	
100mm Diameter x 16mm Bore Max 12,400rpm			
P24	0.55kg	-2010K	
P50	0.45kg	-2050K	
P60	0.45kg	-2060K	
115mm Diameter x 22mm Bore Max 11,000rpm			
P36	0.65kg	-2130K	
P60	0.55kg	-2160K	
P100	0.50kg	-2180K	
127mm Diameter x 22mm Bore Max 10,000rpm			
P60	0.70kg	-2260K	
P80	0.60kg	-2270K	
178mm Diameter x 22mm Bore Max 7,000rpm			
P24	1.95kg	-2410K	



Fibre Discs

Al-Ox

Aluminium Oxide General-Purpose Grade

Resin fibre backed sanding discs are designed for a wide range of industrial applications. High speed penetration of tough and high tensile materials combined with long disc life and optimum flexibility ensure York sanding discs give first class performance every time. Recommended for use with all portable grinders and sanders.



Grit	Weight per 100	Order Code YRK-202	
100mm Diameter x 16mm Bore Max 12,400rpm			
P24	0.55kg	-2010K	
P36	0.55kg	-2030K	
P50	0.45kg	-2050K	
P60	0.45kg	-2060K	
P80	0.40kg	-2070K	
P100	0.35kg	-2080K	
P120	0.35kg	-2090K	
115mm Diameter x 22mm Bore Max 11,000rpm			
P24	1.70kg	-2110K	
P36	1.65kg	-2130K	
P50	1.60kg	-2150K	
P60	1.55kg	-2160K	
P80	1.50kg	-2170K	
P100	1.50kg	-2180K	
P120	1.45kg	-2190K	
178mm Diameter x 22mm Bore Max 7,000rpm			
P24	1.95kg	-2410K	
P36	1.80kg	-2430K	
P50	1.55kg	-2450K	
P60	1.55kg	-2460K	
P80	1.40kg	-2470K	
P120	1.30kg	-2490K	

Zirconium Stainless Steel Grade

Zirc

The zirconia grain is supported by grinding additives which lubricate and cool the area being ground and help prevent clogging, prolonging the effective life of the disc. Suitable for use on all types of stainless steels, weld seams castings and other sophisticated metals for extended periods, removing large amounts of metal without excess heat build up.



Grit	Weight per 100	Order Code YRK-202	
115mm Diameter x 22mm Bore Max 13,300rpm			
P36	0.65kg	-4130K	
P60	0.55kg	-4160K	



Flexible Backing Pads

Suitable for use with all portable and air disc grinders and sanders. Recommended for use with York abrasive discs.



To Suit Disc	Thread Size	Weight each	Order Code KEN-280
100mm	M10 x 1.25	60g	-2010K
	M10 x 1.5	60g	-2030K
	3/8" UNF	70g	-2050K
115mm	M10 x 1.5	80g	-2110K
	M14 x 2.0	80g	-2130K
125mm	5/8" UNC	100g	-2210K
	M14 x 2.0	100g	-2230K

To Suit Disc	Thread Size	Weight each	Order Code KEN-280
178mm	5/8" UNC	180g	-2310K
	M14 x 2.0	180g	-2330K
	5/8" UNC Quick Release	150g	-2350K
	M14 x 2.0 Quick Release	150g	-2370K