

icon 200 AND 300

MULTI-
PROCESS

2-YEAR
WARRANTY

100% DUTY
CYCLE @ 40°C

MICRO-
PROCESSOR



**STAR
WELD**

WELDING
PRODUCTS

VS VINCENT INDUSTRIAL SUPPLIES
P.O. BOX 1249 48 INDUSTRIA CRESCENT TEL: 013 692 8151/2/3
WITBANK EXTENSION 25 FAX: 013 692 8154
1035 WITBANK dennis@vincentis.co.za
WEBSITE: <http://www.vincentis.co.za>

MADE IN
SOUTH AFRICA

icon

200 300

MULTI-PROCESS DC WELDING INVERTER

The Starweld Icon range of welding inverters, offer both high performance and portability. The Micro Processor controlled machines, provide a very stable Arc, with adjustments to suit a variety of different types of welding electrodes.

FEATURES

- ★ **Versatile Multi-process Capability** - DC Stick Welding and DC Lift Tig.
- ★ **High Duty Cycle** - Designed to deliver 100% duty cycle at maximum current with ambient temperatures up to 40°C.
- ★ **TIG Arc Control Menu** - An easy start Lift/Tig arc initiation. The start / finish current, the up and down slopes can all be adjusted. There is also a pulsing feature, for welding of thin materials.V
- ★ **Manual Metal Arc Control Menu** - When performing manual metal arc welding, the arc can be adjusted to obtain a softer or more aggressive arc characteristic.
- ★ **Digital Amp Meters** - Bright display of welding amperage, both presetable and actual.
- ★ **Robust Construction** - PC Board components are securely mounted to enable the machine to operate in hazardous environments, including being mounted on generator sets.
- ★ **Two Year Warranty** - Warranty on all parts and labour.



R.D. VINCENT (PTY) LTD REG. NO. 1975/004192/07 Trading as:

VINCENT INDUSTRIAL SUPPLIES

P.O. BOX 1249 WITBANK 1035	48 INDUSTRIA CRESCENT EXTENSION 25 WITBANK	TEL: 013 692 8151/2/3 FAX: 013 692 8154 dennis@vincentis.co.za
----------------------------------	--	--

WEBSITE: <http://www.vincentis.co.za>

AVAILABLE OPTIONS

Wire Feeder



Water Cooler



Undercarriage



Remote Control



Foot Pedal



Volt Loc
VRD



Welding Safety



Technical Specifications	Icon 200	Icon 300
Input Voltage	220V	380V / 525V
Input Current	28A	17.4A / 12A
Rated Output Voltage	28V	32V
Rated Output Current	200A /	300A
Duty Cycle @ 40°C Ambient	100%	100%
Dimension - W x H x L mm	220X270X360	240X280X450
Weight	12kg	17kg

**STAR
WELD** WELDING PRODUCTS