

KENNEDY Industrial Drill Chuck Arbors

Precision machined, fully hardened and ground to give maximum surface contact.

Morse Taper Drive to Jacobs Taper



Description	Overall Length	Weight each	Order Code KEN-442
No.1 MT x 1JT	90mm	70g	-9110K
No.1 MT x 2JT	95mm	80g	-9120K
No.1 MT x 6JT	96mm	100g	-9160K
No.1 MT x 33JT	95mm	90g	-9190K
No.2 MT x 1JT	100mm	150g	-9210K
No.2 MT x 2JT	105mm	160g	-9220K
No.2 MT x 3JT	115mm	220g	-9230K
No.2 MT x 4JT	125mm	370g	-9240K
No.2 MT x 6JT	110mm	180g	-9260K
No.2 MT x 33JT	110mm	180g	-9290K
No.3 MT x 1JT	120mm	310g	-9310K
No.3 MT x 2JT	125mm	330g	-9320K
No.3 MT x 3JT	135mm	380g	-9330K
No.3 MT x 4JT	145mm	520g	-9340K
No.3 MT x 5JT	150mm	680g	-9350K
No.3 MT x 6JT	130mm	340g	-9360K
No.3 MT x 33JT	125mm	340g	-9390K
No.4 MT x 2JT	135mm	700g	-9420K
No.4 MT x 3JT	160mm	730g	-9430K
No.4 MT x 4JT	170mm	860g	-9440K
No.4 MT x 5JT	175mm	1000g	-9450K
No.4 MT x 6JT	155mm	690g	-9460K
No.4 MT x 33JT	155mm	680g	-9490K
No.5 MT x 3JT	190mm	1700g	-9530K

Morse Taper Drive to Threaded



Description	Overall Length	Weight each	Order Code KEN-442
No.1 MT 1/2 x 20	92mm	100g	-1120K
No.1 MT 3/8 x 24	95mm	80g	-1380K
No.2 MT 1/2 x 20	105mm	170g	-2120K
No.2 MT 3/8 x 24	105mm	170g	-2380K
No.2 MT 1/8 x 16	105mm	180g	-2580K
No.3 MT 1/2 x 20	125mm	360g	-3120K
No.3 MT 3/8 x 16	125mm	370g	-3580K

KD Type - Morse Taper Shank to DIN Taper Arbors

Fully hardened and ground Morse Taper to DIN 228. Chuck taper to DIN 238.



Morse Taper	Chuck Taper	Overall length	Order Code KEN-442
No.2 MT	B12	106.5mm	-5220K
No.2 MT	B16	111.5mm	-5260K
No.3 MT	B12	125.0mm	-5320K
No.3 MT	B16	134.0mm	-5360K
No.4 MT	B16	159.0mm	-5420K
No.4 MT	B22	176.0mm	-5460K

KENNEDY Chuck Keys

Suitable for use with all industrial keyed chucks.



Ref No.	For Use With Chuck Number	Weight each	Order Code KEN-441
S2	440-132/440-139	50g	-0040K
	440-146/440-148		
	440-153/440-158		
	440-246/440-248		
	440-464		
S8	440-506/440-508	50g	-0160K
S9	440-510	30g	-0180K

Bridgeport Drive to Jacobs Taper



Description	Overall Length	Weight each	Order Code KEN-442
R8 x 1JT	130mm	420g	-9610K
R8 x 2JT	135mm	440g	-9620K
R8 x 3JT	145mm	510g	-9630K
R8 x 6JT	135mm	450g	-9660K
R8 x 33JT	135mm	460g	-9690K