



# FALL ARRESTORS

Heavy duty MAXIPROTECT Fall Arrest Retractable Lifelines are designed to reduce vertical impact force on the body caused by falling from height.

MAXIPROTECT® Fall Arrestors provide continuous protection against falls. The Fall Arrestor automatically extends and retracts to allow freedom of movement.

MAXIPROTECT® Fall Arrestors are manufactured in a ISO 9001:2008 factory and all products are CE approved. Maximum rated load of 150kg.



Triple pawl brake system



## SPECIFICATIONS - FALL ARRESTORS EN360 APPROVED

Model Number	Type	Dia./Width of rope (mm)	Length (m)	Weight (kg)
FAMP10	Steel wire rope	4.8	10	6.5
FAMP15	Steel wire rope	4.8	15	8.0
FAMP20	Steel wire rope	4.8	20	10.8

- High strength ABS (thermoplastic) casing
- 150kg capacity for operator and tools
- Triple pawl brake system with energy dissipating mechanism
- Lightweight, compact and durable
- Conforms to EN 360:2002 (SANS 50360:2003)
- Minimum static strength 15kN
- Side cable exit for smooth operation and reduced cable wear

- Top anchor point with built-in swivel limits lifeline twisting
- Buffer spring at cable exit protects block and allows for smooth operation
- Lower self-locking snap hook and swivel with built-in impact indicator for connecting directly to the safety harness
- Available in 10M, 15M and 20M wire rope lengths
- Supplied with pull down cord